

Agenda

- Goals
- ABM Introduction & Similar Lab Ventilation Projects
- Roles & Responsibilities / Points of Contact
- Project Overview / Scope of Work
- Project Benefits
- Project Construction Flow & Schedule Update
- Lab Preparation Requirements
- Post-Construction Follow-Up
- Additional Researcher Resources and Communication Process
- Q & A



Overall Goals

- Gain Input and Feedback
- Identify Concerns
- Construction

Progress to Date and Schedule General Overview

- Schedule Commitments
- Q & A





Roles	Responsibility
GT Facilities Design & Construction Key Contact	Kynthia Gaines
School of Biological Sciences Designee	Frank Stewart
School of Chemical & Biomolecular Eng. Designee	Ben Galfond
School of Chemistry & Biochemistry Designee	Angus Wilkinson
School of Civil & Environmental Eng. Designee	Guangxuan Zhu
School of Earth & Atmospheric Sciences Designee	Jean Lynch-Stieglitz
School of Biomedical Engineering Designee	Michelle LaPlaca
Advanced Technology Development Center (ATDC)	Rashida Mickens
Environmental Health & Safety (EHS)	Nazia Zakir, Ryan Lisk
Building Operations team	Rachel Arnold (UAW), Dewayne Roberson (UAW), Todd Clarkson (EST), and Curtis Burnett (EST)
GT Facilities Assoc. Director Analytics and Comm.	Jessica Rose
ABM Building Solutions Key Contacts	Robert Daw

Lab Ventilation Project Overview

- Ford ES&T and U.A. Whitaker Buildings
- 13-month construction period (started 8/12/2019)
- Construction will impact 150 labs



Lab Ventilation Project - ES&T

Convert Labs with TSI controls to TEL controls

- · General Lab Space Changes:
 - · New TEL Room Controller
 - · Purge Button
 - Area Motion Sensor(s)
 - Lab Supply Valve Actuator Change-out (new fast-acting actuator)
 - · New Lab Supply Differential Pressure Sensors and Probes
 - General Exhaust Valve Actuator Change-out (new fast-acting actuator)
 - · New General Exhaust Differential Pressure Sensors and Probes
- · Fume Hoods Changes (when applicable):
 - · TEL Fume Hood Controller
 - TEL Auto-Sash Closer with Occupancy Sensor
 - Lab Exhaust Valve Actuator Change-out (new fast-acting actuator)
 - · New Lab Exhaust Differential Pressure Sensors and Probes
- · Snorkels (Task Exhaust) Changes (when applicable):
 - · New Fast-Acting Actuator
 - · On/Off Wall Switch





Lab Ventilation Project – U A Whitaker

Upgrade Labs with Triatek controls

- · General Lab Space Changes:
 - · New/Upgraded Triatek Room Controller
 - · Area Motion Sensor(s)
 - · Lab Supply Valve Actuator Change-out (new fast-acting actuator)
 - · New Lab Supply Differential Pressure Sensors and Probes
 - General Exhaust Valve Actuator Change-out (new fast-acting actuator)
 - · New General Exhaust Differential Pressure Sensors and Probes
- · Fume Hoods Changes (when applicable):
 - New/Upgraded Triatek Fume Hood Controller
 - · TEL Auto-Sash Closer with Occupancy Sensor
 - Lab Exhaust Valve Actuator Change-out (new fast-acting actuator)
 - · New Lab Exhaust Differential Pressure Sensors and Probes
- Snorkels (Task Exhaust) Changes (when applicable):
 - · New Fast-Acting Actuator
 - · On/Off Wall Switch





Consistent Temperature Setpoint

- 72.5 degrees Fahrenheit with +/- 2.5 degree deadband
- · Subject to lab requirements, determined by Questionnaire
- · 3 degrees Fahrenheit of user adjustability
- Unoccupied setback, wider deadband (+/- 5 degree F)
- Space Ventilation

	Occupied Room	Unoccupied Room
Air Changes Per Hour	6	4

- Occupancy
 - Lab/Space General Hours of Operation: 7AM to 10PM (Mon.-Fri.)
 - Installed area motion sensors will detect occupancy and adjust the space to "occupied", thereby increasing the ventilation rate and adjusting the temperature deadband back to 2.5 degrees F



Lab/Space and Task Equipment Ventilation

GA Tech EHS Lab Safety Manual

	Current	Revised
General Rules	"General purpose hoods shall	"General purpose hoods shall
Regarding Laboratory	operate at 100 linear feet per	operate at 80 linear feet per
Fume Hoods	minute (LFPM) +/- 20%"	minute (LFPM) +/- 20%"

Tested to failure @ 40 FPM during pilot case



Project Benefits

- Consistent pressure and temperature controls
 - · Enable better working conditions
- · Safer, better functioning lab
 - · Consistent environmental conditions
- Install purge button for release of chemicals to increase ventilation rate
- ABM onsite technical support for 10 years to deal with various issues & preventative maintenance
- Reduced carbon footprint for the Institute



Construction Flow

- Bound to a strict 13-month construction period
 - Approx. 3 to 5 labs will be in construction simultaneously at any given time during the 13-month period
- Intent is to concentrate construction efforts on a single floor or wing of the building at a time
 - · Work will move through building floor by floor
- 35 labs in ES&T completed to date (primarily on the floors 2 and L1)
- U A Whitaker construction scheduled to start on January 20, 2020 (ground floor)



Construction Flow

Pre-planning & Scheduling Logistics

(approximately 30 days prior to lab construction)

- A pre-construction lab visit will be required for <u>each lab</u>
 - · May include representatives from Facilities and EHS
- Identify critical information:
 - Research that is sensitive to vibration
 - Hazardous chemical which need special storage
 - Access to experiment during construction
 - · Experiments that cannot be interrupted




Construction Flow

Pre-planning & Scheduling Logistics

(approximately 30 days prior to lab construction)

- Preliminary air flow readings
 - Contractor in lab for approximately two hours, primarily before 10:00 AM
 - · The research teams will not need not be present
 - The research teams do not need to halt any experiments
 - The contractor will be opening up each fume hood to the 18" sash height position.





Lab Preparation Requirements

- All labs with fume hoods and/or task exhaust (snorkels) will be retrofitted
- Lab operations will be interrupted for 7 days
 - · Construction above the ceiling
 - "Day 2" walk-through with research team representative
 - Equipment Commissioning
 - Controls training for research teams (typically Friday prior to turnover)
- Be Construction Ready: Time for Equipment and Chemical removal is not included in the 7 days



Lab Preparation Requirements

- Hoods must be vacated; as well counters on either side (see photograph)
- Storage under does not have to be vacated
- Remove all chemicals, equipment and tools from inside fume hood - Must be empty
- Remove equipment and chemicals from benchtop on either side of fume hoods - Need to access side panels of the fume hood
- Lab benches and equipment will be physically covered by ABM
- ABM can allow occasional visits to lab to check on things, if arranged in advance



ES&T Lab



Georgia Tech





ES&T Lab







Post-Construction Follow Up

- Post-Construction interviews to be held with research teams
 - Evaluate conditions of the lab after construction is completed
 - Validate projected energy savings
 - Feedback on the overall construction process



Researcher Resources During Construction and Communication

- Follow up after Town Hall Meetings
- School-Wide Meetings
- Town Hall/Q & A Meetings
- · Website Communication:
 - Project Overview & Facts
 - Meeting Minutes
 - Updated Construction Schedule

facilities.gatech.edu/lab-vent



